

115V ELECTRIC WINCHES

- Compact winch is designed to operate on standard 115V house current up to 10 Amp draw
- Full power-in and power-out
- Dynamic and automatic full-load mechanical brake
- 6' industrial type pendant control
- Permanently lubricated gearbox requires no lubrication
- Equipped with pulley block to double pulling capacity, extend winch and wire rope life.



STOCK NO.	MODEL	RATED LINE PULL (LBS.) SINGLE LINE	RATED LINE PULL (LBS.) DOUBLE LINE	STALL LOAD (LBS.)	CABLE SPEED CAP. FPM (FULL-NO LOAD)	MOTOR	AMPS (FULL-NO LOAD)	GEAR RATIO	AIRCRAFT CABLE SIZE (ODXL)	DIMENSIONS (LXDXH/IN.)	SHIP WEIGHT (LBS.)	CARTON PACK
182080	EW-10	1000	2000	1500	13-23	.6HP, 115V, 1Ph	10-3	148:1	5/32"x45'	15x5-3/8x5-3/4	20	1
182082	EW-12	1000	2000	2500	9-14	.6HP, 115V, 1Ph	10-4.3	199:1	3/16"x50'	15 1/4x6x6	33	1

GPW SERIES GENERAL PURPOSE WINCHES

- Rugged zinc plated steel construction for corrosion resistance
- 1000 pounds to 2500 pounds capacities
- Great for use on boat trailers and more
- Reinforced frame for extra strength
- Lifetime lubricated drum bushing and gear shaft bearings
- Stainless steel ratchet spring
- Capacity rating is based on one layer of cable on drum, as cable builds on drum capacity decreases
- Cable not included



STOCK NO.	MODEL	WINCH LOAD CAP. (LBS.)	GEAR RATIO	FREEWHEEL RATCHET POSITION	HAND BREAK	HANDLE LENGTH (IN.)	HUB DIA. (IN.)	REEL 5/16" ROPE	CAP'Y (FT) 3/8" ROPE	7/16" ROPE	1/2" ROPE	3/16" CABLE	1/8" CABLE	SHIP WEIGHT (LBS.)	CARTON PACK
181000	GPW-1000	1000	4.2:1	Off	No	8	1	55	35	25	-	100	215	6	1
181200	GPW-1200	1200	4.2:1	Center	No	8	1	55	35	25	-	100	215	6	1
181400	GPW-1400	1400	4.2:1	Center	No	8	1	55	35	25	-	100	215	7	1
182000	GPW-2000	2000	4.6/11.1	Center	No	11	1	55	35	25	-	100	215	15	1
182500	GPW-2500	2500	5.1:1/12.1:1	Center	Yes	11	1	-	60	35	25	100	-	16	1

JET MATERIAL HANDLING