

AH SERIES PNEUMATIC HOISTS

- Designed for commercial applications where air power is preferred
- 1/4-ton to 1-ton capacities
- 10' and 20' lifts standard, custom length lifts available
- Rugged yet lightweight aluminum construction
- Self-cooling 100% duty-cycle motor will not overheat
- Variable speed pull-cord control for precise load spotting
- Automatic brake system is tail mounted for easy inspection
- Upper and lower limit switches prevent over-travel
- Pendant control option for single-hand operation
- Equipped with heavy-duty chain container
- Proof tested with test certificate
- Compliance: OSHA, ANSI/ASME B30.16 and HST-5 standards

OPTIONAL ACCESSORIES

- Trolleys
- Beam Clamps
- Slings
- Pendant controls
- Chain Bucket



105971



JET MATERIAL HANDLING

STOCK NO.	MODEL	CAPY (LBS)	AIR PRESSURE	NO. OF FALLS	AIR CONSUMPTION (CFM)	HEADROOM (IN.)	STANDARD LIFT (FT.)	AIR INLET (NPT)	NETWT (LBS.)
			(PSI) / LIFTING SPEED @ RATED LOAD (FPM)						
105970	AH-25C-10	550	85/59; 70/53; 57/46	1	71/53/36	17-1/8	10	1/2	51
105971	AH-50C-10	1100	85/39; 70/33; 57/26	1	71/53/36	17-1/8	10	1/2	51
105972	AH-50C-20	1100	85/39; 70/33; 57/26	1	71/53/36	17-1/8	20	1/2	52
105973	AH-100C-10	2200	85/20; 70/16; 57/13	2	71/53/36	20-7/8	10	1/2	57
105974	AH-100C-20	2200	85/20; 70/16; 57/13	2	71/53/36	20-7/8	20	1/2	69

AIR HOIST PENDANT CONTROLS

- Fits models AH-25C, AH-50C, AH-100C
- Available in 6', 11', and 16' lengths for retrofit in the field



STOCK NUMBER	MODEL	LENGTH (FT.)	NETWT. (LBS.)
105985	AHP-10	6	5
105987	AHP-20	16	8

CHAIN BUCKETS

- Rugged weatherproof vinyl construction



STOCK NUMBER	MODEL	DESCRIPTION	NETWEIGHT (LBS.)
105901	CB-A	For all model 10' lifts	2
105902	CB-B	For AH-25C/50C to 39' and 100C to 19'	4
105903	CB-C	For AH-25C/50C to 65' and 100C to 32'	5