



**AT SERIES PNEUMATIC TROLLEY**

- Air trolley comes equipped with 6' pendant control
- Use with air hoists: AH-25C, AH-50C or AH-100C

STOCK NO.	MODEL	CAP'Y (LBS.)	FLANGE WIDTH (IN.) (FPM)	MIN. BEAM RADIUS (IN.)	AIR PRESSURE (PSI)	HEADROOM (IN.)	TRAVELING SPEED W/RATED LOAD (RPM)	AIR CONSUMPTION (CFM)	AIR INLET (NPT/IN.)	NET WEIGHT (LBS.)
252200	AT-1000	2200	3-5	59	57, 70, 85	4-3/4	77, 88, 98	12, 15, 18	3/8	57

**HEAVY-DUTY GRIP PULLERS**



- Industrial quality grip puller designed to lift, lower, or pull heavy loads
- 3/4-ton to 3-ton capacities
- Easy-to-use in any direction, angle, or length of pull or lift
- Multiple clutch brake system holds load in any position
- Safety shear pin in telescopic handle provides automatic overload protection
- Heavy-duty safety hooks with spring-loaded latches
- Available with or without 66 feet of wire rope
- Compliance: ANSI/ASME B30.21 standards

**OPTIONAL ACCESSORIES**

- Replacement wire rope with safety hook
- Snatch blocks
- Beam Slings
- Trolleys
- Slings

*NOTE: Not for use in an explosive environment*

STOCK NO.	MODEL	DIAMETER (IN.)	NET WEIGHT (LBS.)
186576	WR-75	5/16	15
186516	WR-150	7/16	28
186531	WR-300	5/8	41



STOCK NO.	MODEL	PULLING CAP'Y (LBS.)	LIFTING CAP'Y (LBS.)	HANDLE LENGTH (IN.)	DIST PER STROKE (IN.)	DIMENSIONS (LXHXW/IN.)	WIRE ROPE (DIA/IN.)	SPEED PER MIN (FPM)	NET WEIGHT (LBS.)
186575K	JG-75	2750	1650	29-1/2	2-9/32	18-3/16 x 7-5/8 x 4-3/8	5/16	10	36
186515K	JG-150	5500	3300	41	2-3/8	23-5/8 x 9-3/8 x 5-5/8	7/16	10	48
186530K	JG-300	11,000	6600	46-1/2	1-1/2	27-3/4 x 9 x 6	5/8	10	123