

JASJ SERIES AIR/HYDRUALIC SERVICE JACK

- Equipped with a labor-saving air pump and a high-speed cylinder piston that increases lifting speeds and efficiency
- Suitable for use on large trucks
- 3-1/8" extension screw height
- Lifting time with rated load 120 seconds; 35 seconds with no load
- 90 to 150PSI, 3HP compressor required



STOCK NO.	MODEL	CAPACITY (TON)	MINIMUM HEIGHT (IN.)	MAXIMUM HEIGHT (IN.)	SADDLE (DIA./IN.)	OVERALL LENGTH (IN.)	OVERALL WIDTH (IN.)	HANDLE LENGTH (IN.)	SHIP WEIGHT (LBS.)	CARTON PACK
454200C	JASJ-22C	22	8-1/4	20-5/8	2-5/8	41-3/8	12-1/4	41-3/8	110	1

TRANSMISSION JACKS

- Designed for the removal and installation of auto and light truck transmissions or transfer cases
- Wide stance steel frame features reinforced steel side plates that double as tool trays
- Heavy-duty steel ball bearing swivel casters
- Fully adjustable saddle, corner brackets and safety chains
- "Quick" lift hydraulic pump for rapid lifting to contact point without load, except TTJ-1000S
- Safety overload and top-of-stroke bypass system provides maximum pump protection
- Pump handle swivels 360° for operation in any position
- Convenient foot pedal pump featured on TTJ-1000S
- Proof tested and certified
- Complies with ANSI/ASME PALD-2 standards



STOCK NO.	MODEL	CAPY (LBS.)	MIN. HEIGHT (IN.)	MAX. HEIGHT (IN.)	SIDEWAYS ADJUSTMENT LEFT/RIGHT (DEG.)	BACKWARD / FORWARD (DEG.)	SADDLE SIZE (IN.)	OVERALL DIM. (WXL/IN.)	SHIP WEIGHT (LBS.)	CARTON PACK
450055	TJ-1000	1000	8-1/4	30-1/2	30	60 / 17	12 x 12	19x 34-3/4	137	1
450077	TJ-2000X	2000	8	31	30	17 / 60	7-3/4 x 14-1/8	19x36	188	1
450080	TTJ-1000S	1000	36-3/4	76-5/8	12	46 / 42	14-3/8 x 16-1/2	34x36	160	1

JET MATERIAL HANDLING