



JMJ SERIES MOTORCYCLE/ATV JACK

- Ideal for use with motorcycles, ATVs, riding lawn mowers, etc.
- Convenient foot operated pump and release valve allow use of both hands to position and stabilize vehicle
- All steel construction with rust resistant powder coat finish
- Hydraulic pump features chrome plated ram and safety overload bypass system
- Steel swivel casters with foot brake to prevent movement
- 6-position built-in jack stands to prevent accidental lowering
- 3/8" thick rubber pads protect vehicle frame
- Tow handle with rubber grip included
- Proof tested and certified
- Complies with ANSI/ASME PALD-10 standards



STOCK NO.	MODEL	CAP'Y (LBS.)	MIN. HEIGHT (IN.)	MAX. HEIGHT (IN.)	SADDLE DIMENSIONS (LXW/IN.)	DISTANCE BETWEEN SADDLES (IN.)	SAFETY ARM POSITIONS	STROKES TO REACH MAX. HEIGHT	TOW HANDLE SIZE (ODXL/IN.)	OVERALL SIZE (LXWXH/IN.)	SHIP WEIGHT (LBS.)	CARTON PACK
454355	JMJ-1500	1500	5-1/2	17-3/4	12 x 2-1/2 (2)	8-1/4 Inside, 13-1/8 Outside	6	44	1 x 31	36 x 18 x 14	82	1

FARM JACK



- Multi-purpose jack to lift, push, pull, or clamp
- Rugged steel construction throughout
- Automatic step-by-step operation for raising and lowering load
- Large cast iron base for stability
- Adjustable cast steel top clamp clevis for clamping operations
- Safety shear pin protects lifting saddle and dropping of load if jack is overloaded
- Cast steel large and small runners
- Reversible upright steel bar for long life
- Bar holes will accommodate chains, cables, etc.
- Quick disengage with no load
- Working parts exposed for easy cleaning and lubrication
- Rust resistant powder coat finish on handle



STOCK NO.	MODEL	LIFTING CAP'Y AT 1' (LBS.)	WINCHING/PULLING CAP'Y (LBS.)	CLAMPING CAP'Y (LBS.)	MIN. HEIGHT (IN.)	MAX. HEIGHT (IN.)	LIFT PER HANDLE STROKE (IN.)	BASE DIM. (LXW/IN.)	HANDLE LENGTH (IN.)	SHIP WEIGHT (LBS.)	CARTON PACK
440435	FJ-3-1/2	7000	5000	750	4-1/2	43-3/8	3/4	7 x 4	30	35	1

JET MATERIAL HANDLING