



NEW!

JPNX LEVER HOISTS

- Robust cast handle for the big jobs
- Premium grade lever hoist designed for commercial and industrial applications
- 1/2-ton, 3/4-ton, 1-1/2-ton, and 3-ton models
- 5' and 15' lifts standard, custom length lifts available
- All steel construction with rugged one-piece cast handle
- Completely enclosed Weston type automatic brake system for precise load spotting
- Easy-to-use with single hand operation and control
- Simple design makes routine inspection and maintenance easy
- Freewheeling feature without load for quick load attachment
- Permanently lubricated gears under normal operating conditions
- Premium 100 grade low wear chain resists abrasion
- Drop forged safety hooks swivel 360° for easy rigging
- Proof tested with test certificate
- Complies with OSHA, ANSI/ASME B30.21 and HST-3 Standards

CAUTION

Be sure that the supporting structures and load-attaching devices used in conjunction with this hoist provide an adequate safety factor to handle the rated load plus the weight of the equipment. If in doubt, consult a qualified structural engineer. This equipment is not to be used for lifting, supporting or transporting people, or lifting or supporting loads over people.

IMPORTANT

Before installation, read owner's manual for additional warnings and precautions. Not for use in an explosive environment.

OPTIONAL ACCESSORIES

- Trolleys
- Beam Clamps
- Slings

225675





DIMENSIONS (IN.)

MODEL	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R
JPNX-50-5	4-3/4	2-9/16	2-13/16	2-9/16	7-7/8	2-9/16	1-3/16	3-1/8	9/16	12	1-1/10	1-1/4	4-1/8	1-1/10	1-1/4	10	4-5/16	1-9/16
JPNX-90-15	4-3/4	2-9/16	2-13/16	2-9/16	7-7/8	2-9/16	1-3/16	3-1/8	9/16	12	1-1/10	1-1/4	4-1/8	1-1/10	1-1/4	10	4-5/16	1-9/16
JPNX-75-5	4-15/16	2-3/4	3-1/3	2-5/8	8-3/4	2-3/4	2-7/16	3-7/16	5/8	12-3/8	1-3/16	1-7/16	4-3/8	1-1/4	1-7/16	10	4-5/16	1-9/16
JPNX-75-15	4-15/16	2-3/4	3-1/3	2-5/8	8-3/4	2-3/4	2-7/16	3-7/16	5/8	12-3/8	1-3/16	1-7/16	4-3/8	1-1/4	1-7/16	10	4-5/16	1-9/16
JPNX-150-5	5-3/4	3-1/2	3-5/8	3	10-1/8	3-1/2	2-15/16	4-1/8	7/8	14-3/8	1-7/16	1-3/4	5-1/2	1-7/16	1-3/4	14-3/16	6-5/8	1-3/4
JPNX-150-15	5-3/4	3-1/2	3-5/8	3	10-1/8	3-1/2	2-15/16	4-1/8	7/8	14-3/8	1-7/16	1-3/4	5-1/2	1-7/16	1-3/4	14-3/16	6-5/8	1-3/4
JPNX-300-5	7-5/8	4-1/8	4-1/3	4	12-1/2	4-1/8	3-11/16	4-1/3	1-1/10	19-5/16	1-3/4	2-1/4	6-3/4	1-3/4	2-1/4	14-3/16	6-5/8	1-3/4

STOCK NO.	MODEL	RATED CAPACITY (TON)	STANDARD LIFT (FT.)	MIN. DISTANCE BETWEEN HOOKS (IN.)	NUMBER OF FALLS	LOAD CHAIN (DIA./MM)	LIFT PER FULL TURN (IN.)	LBS PULL TO LIFT CAPACITY (LBS.)	LEVER LENGTH (IN.)	SHIP WEIGHT (LBS)
225650	JPNX-50-5	1/2	5	12	1	5	3-1/2	82	10	13-1/2
225652	JPNX-50-15	1/2	15	12	1	5	3-1/2	82	10	17-1/4
225675	JPNX-75-5	3/4	5	12-3/8	1	6	3/4	40	10	19
225676	JPNX-75-15	3/4	15	12-3/8	1	6	3/4	40	10	24-1/4
225615	JPNX-150-5	1-1/2	5	14-3/8	1	8	7/8	48	14-1/8	32
225616	JPNX-150-15	1-1/2	15	14-3/8	1	8	7/8	48	14-1/8	41
225630	JPNX-300-5	3	5	19-1/4	1	10	5/8	84	14-1/8	52-1/2
225631	JPNX-300-15	3	15	19-1/4	1	10	5/8	84	14-1/8	67-1/4