


HVBS-34VS

SAWS



45°-cut can be adjusted easily



Easy to carry



For each application optimum cutting speed can be adjusted

HVBS-34VS – METAL BANDSAW

- ◆ Stable construction for heavy-duty conditions
- ◆ Easy to carry due to low weight of only 15 kg
- ◆ Optimum working results with most different materials due to infinitely variable speeds
- ◆ Adjustable material stop for series production
- ◆ Cast vice for clamping workpieces precisely
- ◆ Swivels to make 45° mitre cuts
- ◆ Digital motor electronics keeps cutting speed constant
- ◆ Rubber feet provide safe, non-skid stability

Standard equipment


- ◆ Bi-metal saw blade
- ◆ Adjustable stop
- ◆ Variable speed control
- ◆ Service manual and operating tools

Stock number 230V	50000310M
Model	HVBS-34VS
Depth of cut 90°	Ø 85 mm <input type="checkbox"/> 85 mm <input type="checkbox"/> 100 x 75 mm
Depth of cut 45°	Ø 65 mm <input type="checkbox"/> 65 mm
Saw blade dimensions	13 x 0.65 x 1325 mm
Swivelling range	0–45°
Saw roller diameter	160 mm
Blade speeds	variable from 30–80 m/min
Motor power input: P_i	850 W/S _e 40%
Weight	15 kg

Accessories



- ◆ 708597 Closed stand with mobile base and tool rest



- ◆ 50000311 Bi-metal saw blade 8/12 TPI for steel/stainless up to 45 HRC
- ◆ 50000312 Bi-metal saw blade 18 TPI for chromium steel