


## HVBS-34VS

## SAWS



45°-cut can be adjusted easily



Easy to carry



For each application optimum cutting speed can be adjusted

## HVBS-34VS – METAL BANDSAW

- ◆ Stable construction for heavy-duty conditions
- ◆ Easy to carry due to low weight of only 15 kg
- ◆ Optimum working results with most different materials due to infinitely variable speeds
- ◆ Adjustable material stop for series production
- ◆ Cast vice for clamping workpieces precisely
- ◆ Swivels to make 45° mitre cuts
- ◆ Digital motor electronics keeps cutting speed constant
- ◆ Rubber feet provide safe, non-skid stability

## Standard equipment


- ◆ Bi-metal saw blade
- ◆ Adjustable stop
- ◆ Variable speed control
- ◆ Service manual and operating tools

<b>Stock number 230V</b>	<b>50000310M</b>
<b>Model</b>	HVBS-34VS
<b>Depth of cut 90°</b>	Ø 85 mm <input type="checkbox"/> 85 mm <input type="checkbox"/> 100 x 75 mm
<b>Depth of cut 45°</b>	Ø 65 mm <input type="checkbox"/> 65 mm
<b>Saw blade dimensions</b>	13 x 0.65 x 1325 mm
<b>Swivelling range</b>	0–45°
<b>Saw roller diameter</b>	160 mm
<b>Blade speeds</b>	variable from 30–80 m/min
<b>Motor power input: P<sub>i</sub></b>	850 W/S <sub>e</sub> 40%
<b>Weight</b>	15 kg

## Accessories



- ◆ 708597 Closed stand with mobile base and tool rest



- ◆ 50000311 Bi-metal saw blade 8/12 TPI for steel/stainless up to 45 HRC
- ◆ 50000312 Bi-metal saw blade 18 TPI for chromium steel