

## SLT-660F



### SLT-660F SCISSOR LIFT TABLE

- ◆ Easy-to-use hydraulic foot pump raises table to multiple heights
- ◆ Safety overload and top-of-stroke bypass system provides maximum pump protection
- ◆ Patent pending pump release handle, feature fold-down handles

<b>Stock number 230V</b>	<b>140777</b>
<b>Model</b>	SLT-660F
<b>Capacity</b>	300 kg
<b>Max. height</b>	825 mm
<b>Min. height</b>	270 mm
<b>Table length</b>	825 mm
<b>Table width</b>	500 mm
<b>Overall length</b>	1080 mm
<b>Overall width</b>	500 mm
<b>Handle height</b>	960 mm
<b>Weight</b>	71 kg

# TRANSPORT

## PT-2048W



### PT-2048W - PREMIUM HAND PALLET TRUCK

- ◆ Premium quality, 2500 kg capacity, robotic weld
- ◆ Extreme control comfort featuring large, ergonomic handles, fingertip control and a 200° steering arc
- ◆ The handle automatically returns to a vertical position (see illustration)
- ◆ Load-tested hydraulic pump unit made in one casting, high-quality seals, hardened and chromeplated hydraulic cylinder
- ◆ Solid steel forks, no need for periodic adjustments
- ◆ Tapered fork tips with nylon wheels for easy entry and exit
- ◆ Steering wheels with polyurethane coating for silent operation
- ◆ Polyamide load rollers with maintenance-free rolling bearings

<b>Stock number</b>	<b>140072</b>
<b>Model</b>	PT-2048W
<b>Overall width W<sub>1</sub></b>	520 mm
<b>Fork width W<sub>2</sub></b>	158 mm
<b>Fork length L<sub>1</sub></b>	1220 mm
<b>Overall length L<sub>2</sub></b>	1638 mm
<b>Max. lifting H<sub>1</sub></b>	196 mm
<b>Min. lifting H<sub>2</sub></b>	73 mm
<b>Steering wheels A</b>	Ø 177 x 50 mm
<b>Load wheels B</b>	Ø 73 x 93 mm
<b>Overall height C</b>	1190 mm
<b>Weight</b>	80 kg

