



Shown with accessories: infeed and outfeed table set (stock-no. 98-1601) and mobile base (stock-no. 98-0130)



Sand up to 405 mm in one pass



Sand up to 810 mm in two pass



75 mm thickness capacity

16-32 PLUS – DRUM SANDER

- ◆ 127x 405 mm extruded aluminium drum, self-cooling, precision machined and balanced
- ◆ Drum operates at 1400 rpm
- ◆ Powerful motor offers the advantages of heavier use for longer periods of time
- ◆ The guaranteed sanding tolerance over the entire sanding width is 0.25 mm
- ◆ An infinitely variable feed rate of 0–3 m/min for maximum sanding results
- ◆ Height adjustment handle allows radical height changes and 1/10 mm adjustments for extremely precise sanding thickness control
- ◆ Drum ball bearings are sealed and permanently lubricated
- ◆ A patented fastener mounted on the inside wall of the drum holds the abrasive strip tight on one side while a spring-loaded mechanism pulls on the other end to remove any slack

- ◆ Stand with shelf
- ◆ One box of ready-to-wrap abrasives
- ◆ Tool

Stock number 230V	629004M
Model	16-32 Plus
Sanding capacity:	
Max. width	405 (810) mm
Min. length	60 mm
Max. thickness	75 mm
Min. thickness	0.8 mm
Drum	Ø 127 x 405 mm extruded aluminium
Infinitely variable feed	0–3 m/min
Speed	1400 rpm
Dust port	100 mm
Motor power output	1.5 HP / S _i 100%
Motor power input	2.6 HP / S _e 40%
Weight	65 kg

Standard equipment

- ◆ One abrasive strip, 80 grit
- ◆ One 100 grit abrasive conveyor belt

Accessories




- ◆ 98-1601 Infeed and outfeed table set



- ◆ 98-0130 Mobile base (4 pcs.)



- ◆ 60-0505 Abrasive strip cleaning stick



- ◆ 60-0316 Conveyor belt 100G

- ◆ 61-0316R Conveyor belt rubber coated