



Digital speed display for quick reading of speed



Set of dead centers which hold a spindle for visual comparison

## 3520B – WOOD LATHE

- ◆ Heavy cast iron legs provide stability at minimum vibrations
- ◆ Adjustable feet guarantee safe stand
- ◆ Robust cast iron headstock, adjustable on machine bed facilitates turning heavy and sturdy work pieces
- ◆ Infinitely variable spindle speeds of 0–3200 rpm via frequency converter in two belt steps for high torque when turning large diameters.
- ◆ Machine bed extension 460 mm (optional) can be mounted in lower position, which gives a max. swing of 1000 mm
- ◆ Spindle stop for simple exchange of face plate and lathe chuck
- ◆ Digital speed display for quick reading of speed
- ◆ Tool storage on machine bed and in tail stock body
- ◆ Centres can hold a sample work piece for visual comparison

### Standard equipment

- ◆ Remote on/off switch
- ◆ 355 mm tool rest
- ◆ 76 mm face plate
- ◆ Drive center
- ◆ Live center
- ◆ Chuck guard

- ◆ Centers to hold sample work piece
- ◆ Tool storages
- ◆ Operating tools and service manual

Stock number 230V	1352001M
Model	3520B
Diameter over bed	508 mm
Center distance	800 mm
Headstock/tailstock taper	MT-2
Tailstock sleeve stroke	115 mm
Speeds: variable	I 0–1200 rpm II 0–3200 rpm
Spindle thread	M 33 x 3.5
Spindle indexing	24x15°, 36x10°
Headstock passage	15,8 mm
Tailstock passage	9,5 mm
Dimensions (LxWxH)	1370 x 690 x 1470 mm
Motor power output	2 HP / S <sub>I</sub> 100%
Motor power input	3.5 HP / S <sub>6</sub> 40%
Weight	326 kg

### Accessories



- ◆ 6294727B Machine bed extension 460 mm with shaft extension for tool rest