



4224 – WOOD LATHE

- ◆ Heavy cast iron legs provide stability at minimum vibrations
- ◆ Adjustable feet guarantee safe stand
- ◆ Spindle provided with two large ball bearings (45 mm)
- ◆ Digital speed display on pivoting headstock for quick reading of speed
- ◆ Maximum torque during low speeds, allows large diameters to be turned. The frequency converter is provided with a resistor brake so that safe and quick stopping is possible
- ◆ Spindle stop for simple exchange of face plate and lathe chuck
- ◆ The poly V-belt transmits full power from motor to spindle and can be adjusted in three positions
- ◆ Main spindle with spindle support on both sides M33 x 3.5 allows bowl turning on left side

Standard equipment

- ◆ Digital display of speeds
- ◆ Positionable on/off switch
- ◆ Stable cast iron machine frame
- ◆ 355 mm tool rest
- ◆ 76 mm face plate
- ◆ Live center

- ◆ Center point
- ◆ Tiltable chuck guard
- ◆ Operating tools and service manual

Stock number 230V	1791254M
Model	4224
Diameter over bed	610 mm
Diameter over tool rest	470 mm
Center distance	1065 mm
Headstock/tailstock taper	MT-2
Tailstock sleeve stroke	115 mm
Speeds: variable	I 0– 900 rpm II 0–1965 rpm III 0–3500 rpm
Spindle thread	M33 x 3.5
Headstock graduation	24 x 15°
Headstock passage	15.8 mm
Tailstock passage	9.5 mm
Dimensions (LxWxH)	1490x654x1720 mm
Motor power output	3 HP / S ₁ 100%
Motor power input	4.8 HP / S ₆ 40%
Weight	410 kg

Accessories



- ◆ 6295846 High tool rest base assembly for outboard turning

- ◆ 6295845 Short bed extension 510 mm (also needed for outboard turning)



- ◆ 6295847 Long bed extension 1650 mm