



Sturdy cast iron table

100 mm dust port

Table tilt 0–45° with 50 mm dust port

Main table tilts with the sanding head for use as a fence in the horizontal position



80S – OSCILLATING EDGE SANDER

- ◆ 150 x 2032 mm – oscillating sanding belt sands in both the horizontal and vertical position or any angle in between
- ◆ 50 oscillations per minute provides a scratch-free finish and prolongs sleeve life
- ◆ Sturdy cast iron table combined with gas cylinder can be easily moved up or down to utilize the full sanding paper
- ◆ The table pivots with the complete machine unit, making it suitable for use as a jointing stop
- ◆ 100 mm dust port for efficient dust collection
- ◆ The belt sander platen features a graphite sheet which helps the unit run cooler giving the machine and the sanding belt much longer life
- ◆ The rubber-coated drive drum provides positive grip and maximum motor-to-belt power transfer
- ◆ The powerful motor is suitable for continuous operation even for hours of steady use
- ◆ Sanding of long pieces is possible after replacing dust port
- ◆ You will find tensioning and tracking the sanding belt to be a simple and quick process

Standard equipment

- ◆ Sanding belt 80 grit
- ◆ 100-mm dust port
- ◆ Mitre gauge
- ◆ Closed stand with tool rest
- ◆ Outer drum support table

Stock number 230 V	1791101M
Stock number 400 V	1791101T
Model	80S
Abrasive belt size	150 x 2032 mm
Max. sanding depth	125 mm
Table tilt	90° to 45°
Belt oscillations per minute	50
Main table size	200 x 750 mm
Abrasive belt speed	9.5 m/s
Motor: 230 V power output	1.5 HP / S ₁ 100%
Motor: 230 V power input	2.6 HP / S ₆ 40%
Motor: 400 V power output	2 HP / S ₁ 100%
Motor: 400 V power input	3.8 HP / S ₆ 40%
Dimensions (LxWxH)	1320 x 560 x 1230 mm
Weight	155 kg