



Simple sanding of curved pieces



Accessory: Abrasive cleaning stick (Stock-no. 60-0505)



2 table inserts with suction slits and 2 table inserts with oblong recess to tilt table standard

JBOS-5 OSCILLATING SPINDLE SANDER

- ◆ Large workspace to handle all your projects
- ◆ Table tilts to 45°
- ◆ The 25 mm spindle oscillating action provides a scratch-free finish and prolongs sleeve life
- ◆ Powerful 0.5 HP motor can accommodate even the heaviest sanding projects
- ◆ Four non-skid rubber feet prevent the machine from moving while in use
- ◆ Oscillation gears are encased in a lubrication box to greatly prolong life and durability
- ◆ Built-in dust port to collect the dust before it becomes airborne

- ◆ 2 oblong table inserts for inclined sanding
- ◆ 100 mm dust port

Standard equipment


- ◆ Complete 6, 12, 16, 38 and 50 mm spindles with sanding sleeve, 100 G
- ◆ 2 round table inserts

Stock number 230V	708404M
Model	JBOS-5
Table size	370 x 370 mm
Max. sanding depth	100 mm
Table tilt	0–45°
Spindle speed	1400 rpm
Oscillations	30/min
Oscillation stroke	25 mm
Motor power output	0.5 HP / S ₁ 100%
Motor power input	0.9 HP / S ₆ 40%
Weight	35 kg

Accessories




- ◆ 708597 Closed stand with mobile base and tool rest



- ◆ 709539 Table insert 76 mm



- ◆ 709538 Rubber-coated drum 76 mm



- ◆ 709534 Spindle 76 mm with sanding sleeve 100G