



JDR-34 / JDR-34F RADIAL DRILL PRESSES

- ◆ Precision cast iron table
- ◆ Lockable magnetic switch
- ◆ 1–16 mm quick clamping chuck with chuck guard standard
- ◆ 80 mm spindle travel with adjustable drill depth stops
- ◆ Powerful 600-W induction motor for continuous operation
- ◆ 5 spindle speeds 500–2500 rpm
- ◆ 410 mm max. distance to column
- ◆ Head can be tilted 45° to the right and 90° to the left
- ◆ Cross laser for easy operation standard

Standard equipment

- ◆ 16 mm quick-clamping chuck
- ◆ Arbor MT-2/B16
- ◆ Chuck guard
- ◆ Cross laser with transformer and On/Off switch
- ◆ Belt cover with limit switch
- ◆ Operating instructions and operating tool

Stock number 230V	10000390M	10000395M
Model	JDR-34	JDR-34F
Distance spindle column	155–410 mm	155–410 mm
Spindle travel	80 mm	80 mm
Spindle taper	MT-2	MT-2
Quick-clamping chuck	1–16 mm	1–16 mm
Column diameter	60 mm	73 mm
Table size	220 x 230 mm	Ø 300 mm
Speeds: 5	500–2500 mm	500–2500 mm
Base size	345 x 210 mm	280 x 480 mm
Motor power output: P₁	0.5 HP / S ₁ 100%	0.5 HP / S ₁ 100%
Motor power input: P₂	0.85 HP / S ₆ 40%	0.85 HP / S ₆ 40%
Weight	42 kg	61 kg

Accessories



- ◆ 10000391 Machine stand for JDR-34



- ◆ 10000371 Drill vise 100 x 100 mm