



Rapid change from planing to thicknessing



Eccentric rapid adjustment of the infeed table



Double guided jointing fence, tilts at the table

JPT-410 / JPT-310 / JPT-260 PLANER THICKNESSER

- ◆ Dual opening of the tables to change from planing to thicknessing in seconds
- ◆ Cast iron jointer tables, precision planed to ensure optimum sliding of the workpieces
- ◆ Eccentric rod support on outfeed table facilitates hollow joint adjustment (JPT-410, JPT-310)
- ◆ Feed can be switched off

Standard equipment

- ◆ Set of three high-speed steel knives
- ◆ 100 mm dust port (JPT-310, JPT-260)
- ◆ 120 mm dust port (JPT-410)
- ◆ Precision fence
- ◆ Adjustable cutter head guard
- ◆ Push wood handle

Stock number 230V	10000290M	10000289M	
Stock number 400V	10000295T	10000289T	
Model	JPT-410	JPT-310	JPT-260
Length of jointer table	1660 mm	1400 mm	1120 mm
Cutterhead diameter	70 mm	70 mm	70 mm
Max. planing width	407 mm	307 mm	256 mm
Length of thicknessing table	600 mm	540 mm	540 mm
Planing thickness	3–225 mm	3–225 mm	3–225 mm
Chip removal (planer)	3 mm	3 mm	3 mm
Chip removal thicknesser	4.5 mm	4.5 mm	4.5 mm
Number of knives	3	3	3
Cutterhead speed	5500 rpm	5500 rpm	5300 rpm
Feed speed	7 m/min	7 m/min	5.5 m/min
Motor: 230 V power output	3 HP / S ₁ 100%	2.3 HP / S ₁ 100%	2.3 HP / S ₁ 100%
Motor: 230 V power input	4.7 HP / S ₆ 40%	3.6 HP / S ₆ 40%	3.6 HP / S ₆ 40%
Motor: 400 V power output	4 HP / S ₁ 100%	3 HP / S ₁ 100%	2.3 HP / S ₁ 100%
Motor: 400 V power input	6 HP / S ₆ 40%	4.7 HP / S ₆ 40%	3.6 HP / S ₆ 40%
Weight	330 kg	230 kg	170 kg

Accessories

- ◆ 10000296 Mobility kit with tommy bar (JPT-410)
- ◆ 708118 Mobile base up to 250 kg (JPT-260, JPT-310)
- ◆ 10000208 High-speed steel knives 410x25x3mm (3-piece set)
- ◆ 10000205 High-speed steel knives 310x25x3mm (3-piece set)
- ◆ 10000287 High-speed steel knives 260x25x3mm (3-piece set)



- ◆ 10000291 Digital thickness display