




Sturdy cast iron sliding table with linear guide and adjustment screws for easy, accurate set-up.



Advantages of tilting to the left:  
Cleaner cut from above.  
No collision with fence.  
Workpiece cannot get jammed when cutting at the fence.

## JTS-250CS – CIRCULAR SAW

The JET SUPERSAW is a better saw.  
With better specs. And a better price.


- ◆ Precision-ground, abrasionproof cast iron wings, just like the professional models
- ◆ Sawblade tilts to the left for safe operation at the fence and a lower risk of backlash for mitred cuts
- ◆ New Micro Glide fence with integrated micro adjustment and magnified cursor for greater precision and even more control comfort
- ◆ The JET SUPERSAW combines the features of an industrial saw with increased specification at excellent value for money
- ◆ Precision mitre gauge fence 0°/90°/135° adjustable. Adjustable fences
- ◆ A rugged steel cabinet guarantees stability for vibration free operation
- ◆ Durable powder coated finish (like all JET models) to make sure your JET SUPERSAW will look good for years

### Standard equipment

- ◆ Table extension 435 x 500 mm
- ◆ Carbide tip saw blade 40-tooth
- ◆ Connecting tube incl. Y-fitting

<b>Stock number 230V</b>	<b>708781KM</b>
<b>Stock number 400V</b>	<b>708781KT</b>
<b>Model</b>	JTS-250CS
<b>Cast iron table</b>	705 x 685 mm
<b>Blade diameter</b>	250 mm
<b>Bore diameter</b>	30 mm
<b>Max. depth of cut at 90°</b>	82 mm
<b>Tilting range of blade</b>	90°–45° left
<b>Width of cut</b>	790 mm
<b>Blade speed</b>	4300 rpm
<b>Dust port diameter</b>	100 mm
<b>Cast iron slide</b>	355 x 685 mm
<b>Sliding table max. width of cut in front of saw blade</b>	725 mm
<b>Motor: 230 V power output</b>	1.75 HP / S: 100%
<b>Motor: 230 V power input</b>	3.1 HP / S: 40%
<b>Motor: 400 V power output</b>	3 HP / S: 100%
<b>Motor: 400 V power input</b>	5.7 HP / S: 40%
<b>Weight</b>	190 kg

### Accessories



- ◆ 708118 Mobile base up to 250 kg
- ◆ 708119 Mobile base up to 500 kg



- ◆ 10000050 Circular saw blade Ø 250 40-tooth