



JTSS-1500



Precision sliding carriage



Scoring unit standard

JTSS-1500 – PANEL SAW

- ◆ Due to its overall size the ideal machine for your small work shop
- ◆ Cleaner cut by serial scoring unit
- ◆ Heavy-duty, torsion-proof sliding table made of anodized, extruded aluminium
- ◆ Heavy cast iron table; table length/width extension standard
- ◆ Heavy cast iron saw unit, easy adjustment via big handwheels
- ◆ Precision mitre gauge with adjustable stops $-45^{\circ}/90^{\circ}/+45^{\circ}$
- ◆ Precision rip fence with integrated micro adjustment

Standard equipment

- ◆ Carbide tip saw blade \varnothing 315/30, 48-tooth
- ◆ Carbide tip scoring saw blade \varnothing 80/20 mm, 20-tooth
- ◆ 800 x 550 mm table length extension
- ◆ 830 x 400 mm right table extension
- ◆ 500 x 500 mm outrigger table, can be dismantled
- ◆ Mitre fence with work stop (1020 mm)
- ◆ Panel stop
- ◆ Workpiece hold-down

Stock number 230V	10000020M
Stock number 400V	10000020T
Model	JTSS-1500
Table size	840 x 550 mm
Sliding carriage	1500 x 350 mm
Sliding table stroke	1750 mm
Max. length of cut	1650 mm
Max. blade diameter	315 mm
Max. depth of cut $90^{\circ}/45^{\circ}$	102 / 81 mm
Blade speed	4000 rpm
Blade tilt	$90^{\circ}/45^{\circ}$
Max. cutting width	850 (1270) mm
Scoring blade diameter	80 / 20 mm
Scoring blade speed	8000 rpm
Dust port diameter	100 mm
Motor: 230 V power output	3 HP / S ₁ 100%
Motor: 230 V power input	5 HP / S ₆ 40%
Motor: 400 V power output	4 HP / S ₁ 100%
Motor: 400 V power input	6.5 HP / S ₆ 40%
Weight	403 kg

Accessories



- ◆ 10000021 Right extension wing 830 x 950 mm for max. 1270 mm cutting width



- ◆ 10000023 Outrigger table 650 x 850 mm with telescopic arm & pull-out mitre fence 2500 mm