



JTSS-3000 – PANEL SAW

- ◆ Due to the long sliding carriage stroke, the machine is a universal tilting arbor saw table
- ◆ Precision-design cast iron table and large table length extensions and table width extensions
- ◆ Outrigger table with telescopic arm and pullout mitre fence with stops for machining large workpieces
- ◆ Mitre fence $\pm 45^\circ$ pivoting with precisely adjustable 90° stops
- ◆ Rip fence can exactly be set to the millimetre via round bar guide and integrated micro adjustment
- ◆ Proven sliding carriage guide system ensures clean cut
- ◆ Durable powder-cut finish to make sure your JET tilting arbor saw table will look good for years
- ◆ High operating safety and unrivalled price/benefit ratio due to sophisticated JET technology

Standard equipment

- ◆ Carbide tip saw blade $\varnothing 315/30$ mm, 48-tooth
- ◆ Carbide tip scoring saw blade $\varnothing 80/20$ mm, 20-tooth
- ◆ 800 x 550 mm table length extension
- ◆ 830 x 950 mm right table extension
- ◆ 1150 x 650 mm outrigger table with telescopic arm


- ◆ Pull-out mitre fence (3200 mm)
- ◆ Panel stop
- ◆ Workpiece hold-down

Stock number 230V	1000030T
Model	JTSS-3000
Table size	840 x 550 mm
Sliding carriage	3000 x 350 mm
Sliding table stroke	3000 mm
Max. length of cut	3150 mm
Max. blade diameter	315 mm
Max. depth of cut $90^\circ/45^\circ$	102 / 81 mm
Blade speed	4000 rpm
Blade tilt	$90^\circ / 45^\circ$
Max. cutting width	1270 mm
Scoring blade diameter	80 / 20 mm
Scoring blade speed	8000 rpm
Dust port diameter	100 mm
Motor power output	5.5 HP / S ₁ 100%
Motor power input	8.5 HP / S ₆ 40%
Weight	570 kg

Accessories



- ◆ 1000022
Digital display for
rip fence
(JTS-1500 + JTS-3000)



- ◆ 1000031
Outrigger table
500 x 500 mm



- ◆ 1000032
Mitre fence with
work stop 1020 mm