


Quick clamping lever and blade tension adjustment on the back of the machine



Upper and lower precision roller guide

JWBS-14 – BANDSAW 355 mm


- ◆ Exclusive design with quick clamping lever to release the blade when not in use
- ◆ Rack guide with millimeter scale for accurate adjustment of the upper blade guide
- ◆ Machine body in solid weld design for smooth operation of guiding rollers
- ◆ T-style rip fence assembly with re-saw attachment (Single point fence allows perfect parallel curve cutting)
- ◆ Precision table with polished cast iron surface, tilts $-10^\circ / 0^\circ / +45^\circ$
- ◆ Steel base
- ◆ 100 mm dust port
- ◆ Upper and lower blade guides extend blade life

Standard equipment

- ◆ Quick blade tensioning lever
- ◆ On/Off switch with no voltage release
- ◆ Mitre cutting guide $\pm 60^\circ$
- ◆ 100 mm dust port
- ◆ Precision fence with parallel cutting device
- ◆ "BG" dust emission inspected

Stock number 230V	10000100M
Model	JWBS-14
Depth of cut	200 mm
Width of cut	350 mm
Min. blade	3 mm
Max. blade	25 mm
Blade length	2560 mm
Table size	500 x 385 mm
Table tilt	$-10^\circ / 0^\circ / 45^\circ$
Adjustable stop at	90°
Wheel diameter	355 mm
Blade speed	800 m/min
Overall dimensions in mm	770 x 650 x 1800
Motor power output	0.75 HP / S _i 100%
Motor power input	1.3 HP / S _e 40%
Weight	90 kg

Accessories



- ◆ 708118 Mobile base up to 250 kg



- ◆ 10000103 Bandsaw blade 3 mm/0.5
- ◆ 10000104 Bandsaw blade 6 mm/0.5
- ◆ 10000105 Bandsaw blade 10 mm/0.5
- ◆ 10000110 Bandsaw blade 16 mm/0.5
- ◆ 10000115 Bandsaw blade 20 mm/0.5