



Spindle indexing every 15°



Machine light

JWL-1220 – WOOD LATHE

- ◆ Heavy-duty cast iron lathe bed ensures stability and minimal operating vibration
- ◆ Heavy-duty cast iron headstock and tailstock provide rigidity, strength and years of trouble-free operation
- ◆ Tailstock is hollow allowing 9 mm long hole boring
- ◆ Quick release levers allow for easy & accurate positioning of tool rest and tailstock
- ◆ Powerful motor suitable for continuous operation – with 6 spindle speeds ranging from 400 to 3300 rpm for maximum results
- ◆ Convenient adjustment handle at the front machine side or potentiometer to quickly change speeds
- ◆ Solid rubber feet to eliminate movement while in operation
- ◆ Solid tailstock contains live center with a full 50 mm ram capacity

- ◆ Face shield
- ◆ Spur center and tooling knockout
- ◆ Adapter M 33 x 3,5
- ◆ Handel
- ◆ Tool storage

Standard equipment

- ◆ Machine light
- ◆ 150-mm-Tool rest
- ◆ 250-mm-Tool rest
- ◆ Live center
- ◆ 75-mm-Face plate

Stock number 230V	708376M
Model	JWL-1220
Swing over bed	305 mm
Center distance	510 mm
Spindle thread	1" x 8 TPI (M 33 x 3,5)
Spindle indexing	24 x 15°
Headstock taper	MK-2
Tailstock taper	MK-2
Speeds: 6	400, 700, 1000, 1500, 2200, 3300 U/min
Motor poer output	0.75 HP / S ₁ 100%
Motor power input	1 HP / S ₂ 40%
Weight	45 kg

Accessories



- ◆ 708377
Machine bed extension 710 mm



- ◆ 708378
Machine stand



- ◆ 708379
Extension for machine stand