



Headstock division every 15°, adapter M 33 x 3.5 standard



Pivoting headstock quickly turns and locks to facilitate outboard turning and to provide better vision during internal machining



Various spindle speeds ranging from 450–2500 rpm

JWL-1236 – WOOD LATHE

- ◆ Heavy-duty cast iron lathe bed ensures stability and minimal operating vibration
- ◆ Pivoting headstock turns 90° and locks to facilitate outboard turning
- ◆ Specially designed lathe bed extension allows easy positioning of outboard turning tool rest
- ◆ Various spindle speeds ranging from 450–2500 rpm
- ◆ Quick release levers allow for easy & accurate positioning of tool rest and tailstock
- ◆ Powerful motor for continuous operation

Standard equipment


- ◆ Rigid stand
- ◆ 300 mm tool rest
- ◆ 150 mm face plate
- ◆ Center point
- ◆ Live center
- ◆ Face shield
- ◆ Adapter M 33 x 3.5

Stock number 230V	708352M
Model	JWL-1236
Swing over bed	300 mm
Center distance	850 mm
Headstock taper	MT-2
Tailstock taper	MT-2
Tailstock ram travel	50 mm
Speeds: 6	450, 700, 1000, 1300, 1700, 2500 rpm
Motor power output	0.75 HP / S _i 100%
Motor power input	1.3 HP / S _e 40%
Weight	85 kg

Accessories



- ◆ 708341 Tool rest 150 mm
- ◆ 708336 Tool rest 300 mm



- ◆ 709160 High-speed tool set (Set of 3 pcs.)