




Micro-adjustment fence



Standing ring milling device



Accessory: Exchange milling spindle 30 mm (Stock-no. 10000251)

JWS-34KX – SPINDLE MOULDER

- ◆ Large cast-iron table with polished surface
- ◆ Fully enclosed welded steel base
- ◆ Accurate spindle height adjustments are possible with the large handwheel
- ◆ Interchangeable spindle with 30 mm shaft and router bit collets are provided
- ◆ Micro-adjustment fence features a 100 mm dust port
- ◆ Column guides to hold down the workpiece
- ◆ Poly V-belt for easy change of 4 speeds – 1700 / 3500 / 6000 / 8000 rpm
- ◆ Easy-to-read speed display through window
- ◆ Spindle indexing for operator-friendly tool change
- ◆ Sanding sleeves from the JET JOVS-10 can be attached to sand cut parts
- ◆ Tenon cutting slide can be mounted as an accessory

Standard equipment

- ◆ 30 mm spindle
- ◆ Collet holder with 8 and 12 mm (8 mm and 1/2" for U.K.) router collets for interchangeable spindle
- ◆ Workpiece hold-downs
- ◆ Micro-adjustment fence
- ◆ Ring fence
- ◆ Mitre gauge
- ◆ "BG" dust emission inspected

Stock number 230V	708502KXM
Stock number 400V	708502KXT
Model	JWS-34KX
Spindle speed	1700 / 3500 / 6000 / 8000 rpm
Table size	540 x 635 mm
Spindle diameter	30 mm
Spindle stroke	80 mm
Clamped height	70 mm
Table opening	160 mm
Max. tool height over table	120 mm
Max. tool diameter	180 mm
Router bit collet size	8 and 12 mm
Motor: 230 V power output	2 HP / S ₁ 100%
Motor: 230 V power input	3.5 HP / S ₆ 40%
Motor: 400 V power output	3 HP / S ₁ 100%
Motor: 400 V power input	5.7 HP / S ₆ 40%
Weight	145 kg

Accessories



◆ 10000252 Sanding set: sanding spindle and drums, Ø 25, 38, 50, 75 and 100 mm, incl. sleeves 80G



◆ 10000253 Tenoning unit

◆ 10000251 Exchange milling spindle 30 mm