




Micro-adjustment fence



Standing ring milling device



Accessory: Exchange milling spindle 30 mm (Stock-no. 10000251)

**JWS-34KX – SPINDLE MOULDER**

- ◆ Large cast-iron table with polished surface
- ◆ Fully enclosed welded steel base
- ◆ Accurate spindle height adjustments are possible with the large handwheel
- ◆ Interchangeable spindle with 30 mm shaft and router bit collets are provided
- ◆ Micro-adjustment fence features a 100 mm dust port
- ◆ Column guides to hold down the workpiece
- ◆ Poly V-belt for easy change of 4 speeds – 1700 / 3500 / 6000 / 8000 rpm
- ◆ Easy-to-read speed display through window
- ◆ Spindle indexing for operator-friendly tool change
- ◆ Sanding sleeves from the JET JOVS-10 can be attached to sand cut parts
- ◆ Tenon cutting slide can be mounted as an accessory

**Standard equipment**

- ◆ 30 mm spindle
- ◆ Collet holder with 8 and 12 mm (8 mm and 1/2" for U.K.) router collets for interchangeable spindle
- ◆ Workpiece hold-downs
- ◆ Micro-adjustment fence
- ◆ Ring fence
- ◆ Mitre gauge
- ◆ "BG" dust emission inspected

| Stock number 230V                  | 708502KXM                     |
|------------------------------------|-------------------------------|
| Stock number 400V                  | 708502KXT                     |
| <b>Model</b>                       | JWS-34KX                      |
| <b>Spindle speed</b>               | 1700 / 3500 / 6000 / 8000 rpm |
| <b>Table size</b>                  | 540 x 635 mm                  |
| <b>Spindle diameter</b>            | 30 mm                         |
| <b>Spindle stroke</b>              | 80 mm                         |
| <b>Clamped height</b>              | 70 mm                         |
| <b>Table opening</b>               | 160 mm                        |
| <b>Max. tool height over table</b> | 120 mm                        |
| <b>Max. tool diameter</b>          | 180 mm                        |
| <b>Router bit collet size</b>      | 8 and 12 mm                   |
| <b>Motor: 230 V power output</b>   | 2 HP / S <sub>1</sub> 100%    |
| <b>Motor: 230 V power input</b>    | 3.5 HP / S <sub>6</sub> 40%   |
| <b>Motor: 400 V power output</b>   | 3 HP / S <sub>1</sub> 100%    |
| <b>Motor: 400 V power input</b>    | 5.7 HP / S <sub>6</sub> 40%   |
| <b>Weight</b>                      | 145 kg                        |

**Accessories**



- ◆ 10000252 Sanding set: sanding spindle and drums, Ø 25, 38, 50, 75 and 100 mm, incl. sleeves 80G



- ◆ 10000253 Tenoning unit

- ◆ 10000251 Exchange milling spindle 30 mm