

Contour sanding with dust collection



EHVS-80 without oscillation

OES-80CS – OSCILLATING EDGE SANDER EHVS-80 – EDGE SANDER


- ◆ Oscillating feature provides a scratch-free finish and reduces heat build-up on sanding belt (OES-80CS)
- ◆ 150x2260 mm sanding belt sands in both the horizontal and vertical position or any angle in between
- ◆ Sturdy cast iron table can be moved up or down to utilize the full sanding paper
- ◆ 100 mm dust port for efficient dust collection
- ◆ The belt sander platen features a graphite sheet which helps the unit run cooler giving the machine and the sanding belt much longer life
- ◆ The powerful motor is suitable for continuous operation even for hours of steady use
- ◆ Sanding of long pieces is possible

Standard equipment

- ◆ Sanding belt 80 grit
- ◆ 100 mm dust port
- ◆ Mitre gauge
- ◆ Closed stand with tool rest
- ◆ Adjustable fence
- ◆ Extension table for contour sanding
- ◆ EHVS-80 without oscillation

Stock number 230V	708447M	708449M
Stock number 400V	708447T	708449T
Model	OES-80 CS	EHVS-80
Fence	110 x 610 mm	110 x 610 mm
Abrasive belt size	150 x 2260 mm	150 x 2260 mm
Max. sanding depth	125 mm	125 mm
Belt tilt	90°	90°
Oscillation per min.	100	–
Table size	180 x 800 mm	180 x 800 mm
Belt speed	16 m/s	16 m/s
Motor: 230V power output	1.5 HP/S ₁ 100%	1.5 HP/S ₁ 100%
Motor: 230V power input	2.6 HP/S ₆ 40%	2.6 HP/S ₆ 40%
Motor: 400V power output	2 HP/S ₁ 100%	2 HP/S ₁ 100%
Motor: 400V power input	3.8 HP/S ₆ 40%	3.8 HP/S ₆ 40%
Weight	120 kg	110 kg

Accessories



- ◆ 708118 Mobile base up to 250 kg



- ◆ 60-0505 Abrasive strip cleaning stick